

Comments

```
//single-line           comment
/* multiline */         comment
/* blah                 comment
/* nested */
blah */
```

If - Else If - Else Example

```
val count = 42
if (count == 42) {
    println ("I have the answer ")
} else if (count > 35 && count < 49) {
    println ("The answer is close")
} else {
    println ("The answer eludes me.")
}
```

When Example

```
val answerString = when {
    count == 42 -> "I have the answer "
    count > 35 -> "The answer is close."
    else -> "The answer eludes me."
}
```

Array Examples

```
// once an array is created the size is fixed
val school = arrayOf("s har k", " sal mon ", " - min now ", 2)
println(java.util.Arrays.toString(school))
//mixed type array
val numbers = intArrayOf(1, 2, 3)
//print array
for (element in school){
    print(element + " ")
}
// concat enate arrays
array3 = array1 + array2
// initialize array with code
val array = Array(5) { it * 2 }
```

elements cannot be added or removed, except by copying to a new array
can loop through elements and index at the same time

Lists

```
// create list, cannot be changed
val school = listOf("ma cke rel ", " tro ut")
// create list, can be changed
val myList = mutableListOf("t una ", " sal - mon ")
myList.remove("shark")
```



By [BeckyIndirectlyToo](#)

cheatography.com/beckyindirectlytoo/

Not published yet.

Last updated 31st August, 2023.

Page 1 of 3.

Sponsored by [ApolloPad.com](#)

Everyone has a novel in them. Finish Yours!

<https://apollopad.com>

Functions Example

```
// create function
var count:Int = 42
fun genera teA nsw erS tri ng(): String {
    val answer String = if (count ==42) {
        "I have the answer."
    } else {
        "The anwer eludes me"
    }
    return answer String
}
```

Anonymous Function Example

```
//Anonymous functions
val string Len gth Func: (String) -> Int = {input -
>
    input.l ength
}
// call anonymous function
val string Length: Int = string Len gth Fun c("A -
ndr oid ")
```

Class Examples

```
//create class
class Car{
    //prop erties
    val wheels = listOf <Wh eel >()
}
```

Data Types

Type	Size(bits)	Values
Byte	8	-128 to 127
Short	16	-32768 to 32767
Int	32	-2 ³¹ to 2 ³¹ -1
Long	64	-2 ⁶³ to 2 ⁶³ - 1

Variable Declaration

```
val count : Int = 10           value can never change
var count : Double = 10.01     value can change
val eFloat : Float = 3.14f     needs the f suffix
val name: String? = null       add ? to make a nullable value
val name : String? = name!!    not-null assertion operator
                                throws exception if full
```

variable interpolation: \$count

Kotlin variables can't hold null values by default.

For Loop Examples

```
// print index and element
for ((index, element) in school.wi thI nde x()){
    printl n("Item at $index is $eleme nt \n")
}
//print range of numbers or letters
for (i in 'a'..'h') print (i)
```



By [BeckyIndirectlyToo](#)

cheatography.com/beckyindirectlytoo/

Not published yet.

Last updated 31st August, 2023.

Page 2 of 3.

Sponsored by [ApolloPad.com](#)

Everyone has a novel in them. Finish Yours!

<https://apollopadd.com>

For Loop Examples (cont)

```
> for (i in 5 downTo 1 step 1.5) print(i)
```

While Examples

```
var bubbles = 0
while (bubbles < 50) {
    bubbles++
}
println("$ bubbles bubbles in the water/ n")
do {
    bubbles--
} while (bubbles > 50)
println("$ bubbles bubbles in the water/ n")
repeat(2) {
    println("A fish is swimmi ng." )
}
```

Function with Argument Example

```
// call function
val answerString = generateAnswerString()

// function with argument
fun generateAnswerString (countThreshold: Int) :String {
    ...
}
return answerString
}

// call function with argument

val answerString = generateAnswerString(42)
```

Void Function Example

```
// void function
fun printSum(a: Int, b: Int): Unit {
    println("sum of $a and $b is ${a + b}")
}
```

Higher-Order Functions

```
// functions that can take functions as arguments
fun string Map per (str: String, mapper: (String)
-> Int): Int {
    //Invoke function
    return mapper (str)
}
/**an onymous function can be called outside the
parent hesis
string Map per ("An dro id") { input ->
    input.l ength
}
```



By [BeckyIndirectlyToo](#)

cheatography.com/beckyindirectlytoo/

Not published yet.

Last updated 31st August, 2023.

Page 3 of 3.

Sponsored by [ApolloPad.com](#)

Everyone has a novel in them. Finish Yours!

<https://apollopadd.com>