

ansible-playbook	
<YAML>	Run on all hosts defined
<YAML> -f 10	Run 10 hosts in parallel
<YAML> -v	Verbosity (-vv, -vvv)
<YAML> -C -D	-C: Dry run -D: Diff
<YAML> -I <host>	Run the playbook against <host>
<YAML> [--list-hosts --list-tasks]	Show [hosts tasks] triggered for each play
<YAML> --syntax-check	Self explanatory
<YAML> --start-at-task "my task"	Start PB at specific task
<YAML> --tags "tag1,tag2"	Only run tasks with tag1 and 2
<YAML> --tags [tag1,tag2]	Only run tasks with tag1 or 2
<YAML> --skip-tags [tag1,tag2]	Skip tasks with tag1 or 2
<YAML> -e "APP_USER=john"	Override variable in your playbook
--become --become-method=doas --become-user=www-data --ask-become-pass	Run the playbook as www-data. Use method <i>runas</i> for windows hosts
... --ask-vault-pass	Ask for the vault pass at runtime
... --vault-password-file <vault_password_file>	If you vault pass is in a file
<YAML> [-C --check]	Dry run

Ansible-galaxy	
[collection role] list	List installed collections or roles
install <galaxy.repo> -p .roles	Install the role into .roles/galaxy.repo folder

ansible	
all -m ping	Check if hosts are reachable
<HOST> -m setup	Gather facts for <HOST>
<HOST> -m setup --tree /tmp/file	Save facts in </tmp/file>
all -m setup -a "filter=ansible_distribution"	Get only specific facts on all hosts
<GROUP> -a "ip a"	Exec arbitrary cmd on hosts

Ansible-vault	
create <fileName>	
edit <fileName>	Will ask you for the password when editor open and encrypt the file
decrypt <fileName>	back when you exit editor
encrypt <fileName>	
view <fileName>	

ansible-config	
list	List all possible configurations
view	Show current config
dump	Display all current config value and where it is set

ansible-inventory [-i INVENTORY]	
--graph	Show inventory graph
--list	Display hosts info
--host <HOST>	Display host info
-i [INVENTORY] -y	Display inventory with processed variables

