

registers

TMOD	G C/T M1 M0 G C/T M1 M0
SCON	SM0 SM1 SM2 REN T8 R8 TI RI
IE	EA - ET2 ES ET1 EX1 ET0 EX0
TCON	F1 R1 F0 R0 IE1 IT1 IE0 IT0

BAUD RATE

Baud Rate	TH1 (Decimal)	TH1 (HEX)
9600	-3	FD
4800	-6	FA
2400	-12	F4
1200	-24	E8

PRIORITY ORDER

Interrupt	number	pin
INT0	0	P3.2
TF0	1	P3.4
INT1	2	P3.3
TF1	3	P3.5
RI+TI	4	P3.0(Rx)+P3.1(Tx)

TIMERS

SET TMOD
INITIALIZE TL , TH
Start Timer TR=1
Poll [While(TF == 0); TR=0; TF=0;]

SERIAL

TMOD = 0X20
TH1= -3 (BAUD RATE)
SCON = 0X50
SBUF= data;
poll/ISR for TI/ RI

INTERRUPT

ISR definition
void fxn() interrupt [] {}
enable interrupts IE



By ganeshtejaGT

cheatography.com/ganeshtejagt/

Published 21st April, 2019.
Last updated 21st April, 2019.
Page 1 of 1.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
<https://apollopadd.com>