

KnockoutJS

1. Inline Component

A. Define

```
ko.components.register(component-name, {
  viewModel: fn(params),
  template: html string
});
```

B. Declare

i. Custom Element

```
<component-name params=""></component-name>
```

ii. Component Binding

```
<div data-bind="component: 'component-name'"></div>
```

```
<div data-bind="component: observable"></div>
```

```
<div data-bind="component: {name: ' ',
  params: {}}"></div>
```

2. External Dependencies Component

A. Define

```
ko.components.register(widget-name, {
  viewModel: { require: moduleid },
  template: { require: 'text!url' }
});
```

KnockoutJS Defining ViewModel

1. Constructor Function

```
function GenericViewModel(params) {
  // 'params' is an object whose key/value
  // pairs are the parameters
  // passed from the component binding or
  // custom element.
  this.someProperty = params.something;
}
ko.components.register('component-name', {
  viewModel: GenericViewModel,
  template: ...
});
```

2. Shared Instance

```
var sharedViewModelInstance = { ... };
ko.components.register('component-name', {
  viewModel: sharedViewModelInstance,
  template: ...
});
```

3. createViewModelFactory

KnockoutJS Defining ViewModel (cont)

```
ko.components.register('component-name',
{
  viewModel: {
    createViewModel: function(params,
    componentInfo) {
      // - 'params' is an object whose key/value
      // pairs are the parameters
      // passed from the component binding or
      // custom element
      // - 'componentInfo.element' is the element
      // the component is being
      // injected into. When createViewModel is
      // called, the template has
      // already been injected into this element,
      // but isn't yet bound.
      // - 'componentInfo.templateNodes' is an
      // array containing any DOM
      // nodes that have been supplied to the
      // component. See below.
      // Return the desired view model instance,
      // e.g.:
      return new MyViewModel(params);
    }
  },
  template: ...
});
```

DOM manipulation should be done in custom bindings

4. AMD ViewModel

```
ko.components.register('component-name',
{
  viewModel: { require: 'some/module/name'
  },
  template: ...
});
```