

Zip Files

tar -cvf sample1.tar /home/sample1dir/
where,
c – Creates a new .tar archive file.
v – Verbosely show the .tar file progress.
f – File name type of the archive file.
Above command creates a "sample1.tar" file by zipping "/home/sample1dir/" directory.

gzip archive

To create a compressed gzip archive file we use the option as z:

tar cvzf sample2.tar.gz /home/sample2dir

or

tar cvzf sample3.tgz /home/sample3dir

tar.bz2 archive

The bz2 feature compress and create archive file less than the size of the gzip. The bz2 compression takes more time to compress and decompress files as compared to gzip which takes less time. To create highly compressed tar file we use option as j.

tar cvfj sample4.tar.bz2 /home/sample4

OR

tar cvfj sample5.tar.tbz /home/sample5

OR

tar cvfj sample6.tar.tb2 /home/sample6

Add Files or directories to tar Archive files

To add files or directories to existing tar archived file we use the option r (append)

tar -rvf sample1.tar xyz.txt

untar archive file

To untar or extract a tar file, just issue following command using option x (extract).

tar -xvf sample1.tar

This command extracts the file in current directory

untar file in different directory

To untar in a different directory then use option as "-C <specified_directory>"

tar -xvf sample1.tar -C /targetDir/

Uncompress Files

tar -xvf sample2.tar.gz Uncompress tar.gz files

tar -xvf sample3.tar.bz2 Uncompress tar.bz2 files

tar -tvf sample1.tar Lists content of tar file (*t- list content*)

tar -tvf sample2.tar.gz Lists content of tar.gz file (*t- list content*)

tar -tvf sample3.tar.bz2 Lists content of tar.bz2 file

Untar single file from tar archive file

To extract only specific file from archive file:

For *.tar:

tar -xvf sample1.tar process.sh

(or)

tar --extract --file=sample1.tar process.sh

For *.tar.gz:

tar -zxvf codedir.tar.gz pom.xml

(or)

tar --extract --file=codedir.tar.gz pom.xml

For *.tar.bz2

tar -jxvf phpfiles.tar.bz2 home/php/index.php

(or)

tar --extract --file=phpfiles.tar.bz2 /home/php/index.php

Untar multiple files

To extract or untar multiple files from the tar, tar.gz and tar.bz2 archive file. For example the below command will extract "file 1" "file 2" from the archive files.

tar -xvf sample1.tar "file 1" "file 2"

tar -zxvf sample2.tar.gz "file 1" "file 2"

tar -jxvf sample3.tar.bz2 "file 1" "file 2"

Extract group of files using wildcard

tar -xvf sample1.tar --wildcards '*.php'

tar -zxvf sample2.tar.gz --wildcards '*.php'

tar -jxvf sample3.tar.bz2 --wildcards '*.php'



By [karthikmgs](#)

Not published yet.

Last updated 26th August, 2017.

Page 1 of 2.

Sponsored by [ApolloPad.com](#)

Everyone has a novel in them. Finish Yours!

<https://apollopadd.com>

Check size of tar file

Following command shows the size of archive file in KB:

```
tar -czf - sample1.tar | wc -c
```

```
tar -czf - sample2.tar.gz | wc -c
```

```
tar -czf - sample3.tar.bz2 | wc -c
```

Tar command attributes

c – create a archive file.

x – extract a archive file.

v – show the progress of archive file.

f – filename of archive file.

t – viewing content of archive file.

j – filter archive through bzip2.

z – filter archive through gzip.

r – append or update files or directories to existing archive file.

W – Verify a archive file.

wildcards – Specify patterns in unix tar command



By [karthikmgs](#)

cheatography.com/karthikmgs/

Not published yet.

Last updated 26th August, 2017.

Page 2 of 2.

Sponsored by [ApolloPad.com](#)

Everyone has a novel in them. Finish Yours!

<https://apollopad.com>