

Data Types

> " -5" into int	converts string to integer
> date now date to-tim ezone " Eur ope /Lo ndo n"	converts present date to provided time zone
> {'name': 'nu', 'stars': 5, 'langu age': 'Python'} upsert language 'Rust'	updates a record's language and if none is specified inserts provided value
> [one two three] to yaml	converts list of strings to yaml
> [{name: 'Robert' age: 34 position: 'Desig ner'} {name: 'Margaret' age: 30 position: 'Software Develo per'} {name: 'Natalie' age: 50 position: 'Accou nta nt'}] select name position	selects two columns from the table and prints their values

Lists

> [foo bar baz] insert 1 'beeze' > \$strin g_list	inserts beeze value at st index in the list
> [1, 2, 3, 4] update 1 10	updates 2nd value to 10
> let numbers = [1, 2, 3, 4, 5] > \$numbers prepend 0	adds value at the beginning of the list
> let numbers = [1, 2, 3, 4, 5] > \$numbers append 6	adds value at the end of the list
> let flowers = [cammomile marigold rose forget -me -not] > let flowers = (\$flowers first 2) > \$flowers	creates slice of the first two values from flowers list
> let planets = [Mars Jupiter Saturn Uranus Neptune] > \$planets each { it \$"(\$it) is a planet of solar system " }	iterates over a list; it is current list value
> \$planets enumerate each { it \$"(\$ it.i ndex + 1) - (\$it.i tem)" } }	iterates over a list and provides index and value in it
> let scores = [3 8 4] > \$"total = (\$scores reduce { it, acc \$acc + \$it })"	reduces the list to a single value, reduce gives access to accumulator that is applied to each element in the list
> \$"total = (\$scores reduce --fold 1 { it, acc \$acc * \$it })"	initial value for accamulator value can be set with --fold
> let planets = [Mars Jupiter Saturn Uranus Neptune] > \$planets.2	gives access to the 3rd item in the list

Lists (cont)

```
> let planets = [Mars Jupiter Saturn Uranus Neptune]           checks if any string in the list starts with E
> $planets | any {|it| $it | str starts -with " E" }
> let cond = {|x| $x < 0 }; [-1 -2 9 1] | take while $cond      creates slice of items that satisfy provided condition
```

Tables

```
> ls | sort-by size                                             sorting table by size of files
> ls | sort-by size | first 5                                   sorting table by size of files and show first 5 entries
> let $a = [
  [a_col b_col c_col]; [foo bar snooze]
]
> let $b = [
  [a_col b_col c_col]; [hex seeze feeze]
]
> $a | append $b                                               concatenates two tables with same columns
> let teams_scores = [                                         removes the last column of a table
  [team score plays]; ['team_1' 311 3] ['team_2', 245 2]
]
> $teams_scores | drop column
```

Files & Filesystem

```
> start file.txt                                               opens a text file with the default text editor
> 'lorem ipsum ' | save file.txt                               saves a string to text file
> 'dolor sit amet' | save --append file.txt                   appends a string to the end of file.txt
> { a: 1, b: 2 } | save file.json                             saves a record to file.json
> glob **/*.{ rs, toml } --depth 2                           searches for .rs and .toml files recursively up to 2 folders deep
> watch . --glob ==* /*.rs {|| cargo test }                  runs cargo test whenever a Rust file changes
```

Custom Commands

```
def greet [name: string] {                                     custom command with parameter type set to string
  $"hello ($name )"
}
def greet [name = " nus hel l"] {                             custom command with default parameter set to nushe11
  $"hello ($name )"
}
```



Custom Commands (cont)

```
def greet [
  name: string
  --age: int
] {
  [$name $age]
}
> greet world --age 10
```

passing named parameter by defining flag for custom commands

```
def greet [
  name: string
  --age (-a): int
  --twice
] {
  if $twice {
    [$name $age $name $age]
  } else {
    [$name $age]
  }
}
> greet -a 10 --twice hello
```

using flag as a switch with a shorthand flag (-a) for the age

```
def greet [...name: string] {
  print " hello all:"
  for $n in $name {
    print $n
  }
}
> greet earth mars jupiter venus
```

custom command which takes any number of positional arguments using rest params

Variables and Subexpressions

```
> let val = 42
> print $val
42
```

an immutable variable cannot change its value after declaration

```
> let val = 42
> do { let val = 101; $val }
101
> $val
42
```

shadowing variable (declaring variable with the same name in a different scope)

```
> mut val = 42
> $val += 27
> $val
69
```

declaring a mutable variable with `mut` key word

```
> mut x = 0
> [1 2 3] | each { $x += 1 }
```

closures and nested defs cannot capture mutable variables from their environment. This expression results in error.

Variables and Subexpressions (cont)

```
> const plugin = 'path/ to/ plugin'
```

```
> register $plugin
```

```
> let files = (ls)
```

```
> $files.na me?.0?
```

a constant variable is immutable value which is fully evaluated at parse-time

using question mark operator to return null instead of error if provided path is incorrect

```
> let big_files = (ls | where size > 10kb)
```

```
> $big_files
```

using subexpression by wrapping the expression with parentheses ()

Modules

```
> module greetings {
  export def hello [name: string] {
    $"hello ($name)!"
  }
  export def hi [where: string] {
    $"hi ($where)!"
  }
}
```

using inline module

```
> use greetings hello
> hello "world"
```

```
# greetings.nu
```

```
export-env {
```

```
  $env.MYNAME = "Arthur, King of the Britons"
```

```
}
```

```
export def hello [] {
```

```
  $"hello ($env.MYNAME)"
}
```

```
> use greetings.nu
```

```
> $env.MYNAME
```

```
Arthur, King of the Britons
```

```
> greetings hello
```

```
hello Arthur, King of the Britons!
```

importing module from file and using its environment in current scope



By **lomm28**

cheatography.com/lomm28/

Not published yet.

Last updated 22nd August, 2023.

Page 4 of 6.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

Modules (cont)

```
# greetings.nu                                using main command in module
export def hello [name: string] {
    $"hello ($name)!"
}
export def hi [where: string] {
    $"hi ($where)!"
}
export def main [] {
    "greetings and salutations!"
}
> use greetings.nu
> greetings
greetings and salutations!
> greetings hello world
hello world!
```

Strings

```
> let name = "Alice"                          prints greetings, Alice!
> $"greetings, ($name)!"

> let string_list = "one,two,three" | split row "," splits the string with specified delimiter and saves the
> $string_list                                list to string_list variable

> "Hello, world!" | str contains "o, w"        checks if a string contains a substring and returns boolean
> $string_list

> let str_list = [zero one two]               joins the list of strings using provided delimiter
> $str_list str join ','

> 'Hello World!' | str substring 4..8         created a slice from a given string with start (4) and
                                                end (8) indices

> 'Nushell 0.80' | parse '{shell} {version}'   parses a string into a table

> "acronym, long \nAPL, A Programming Language" | from csv parses comma separated values (csv)

> $(ansi_purple _bold)This text is a bold purple !(ansi_reset) ' ansi command colors the text (always end with ansi
reset to reset color to default)
```



By **lomm28**
cheatography.com/lomm28/

Not published yet.
 Last updated 22nd August, 2023.
 Page 6 of 6.

Sponsored by **CrosswordCheats.com**
 Learn to solve cryptic crosswords!
<http://crosswordcheats.com>

