

XSD

Atributs:	Default
Fixed	From
Id	Name
Ref	Type
Use	
Types:	String
Decimal	Integer
Boolean	Date
Time	
Repetició:	Sequence
Choice	All

XSLT

```
<template> ---> Sortida
Att:Match de Templa -
te- --> Arrel
<xs l:f or-each select -
=" ">
<xs l:v alue-of select -
=" " />
(for)Att: order- by= " -
+--" OR---> <xs l:sort
select =""/>
<xsl:if test="e xpr -
ess ion "> --> (After
for )
```

Xpath

Selecció nodes

/	De arrel
//	Arrel (no cal direccio)
.	Actual
..	Pare del actual
@	Atribut

Funcions:

last()	posicio Ultim node
position()	posicio node
count(node-set)	nombre de nodes

Xpath (cont)

number sum(no- retorna la de-set) suma

number round 8number)

Predicats:

/bookstore/b- el numero ook[1] indica

/bookstore/book- ultim [last()]

/bookstore/book- penultim [last()-1]

/bookstore/book- tots menys [position()<3] de 3

//title[@lang] tots atribut lang

/bookstore/book- titol de llibre [price- amb >35.00]/title condicio

Xquery

Variables

```
let $resultat := "Hola món!"
return $resultat
```

DOC:

```
let $d := doc('/ Use -
rs/ pal amo s/G oogle
Drive/M4-
```

```
XML/UF 2/m ate ria l/x -
que ry_ int ro/ vid -
eos.xml')
```

```
return $d
```

FOR:

```
for $a in $doc// act -
ors /actor
```

WHERE:

```
where ends-w ith($a,
'Lisa')
```