

XSD	
Atributs:	Default
Fixed	From
Id	Name
Ref	Type
Use	
Types:	String
Decimal	Integer
Boolean	Date
Time	
Repetició:	Sequence
Choice	All

XSLT	
<code><template> ---> Sortida</code>	
<code>Att:Match de Templa -</code>	
<code>te- --> Arrel</code>	
<code><xs l:f or-each select -</code>	
<code>= " " "></code>	
<code><xs l:v alue-of select -</code>	
<code>= " " /></code>	
<code>(for)Att: order- by= " -</code>	
<code>+-" OR---> <xs l:sort</code>	
<code>select =""/></code>	
<code><xsl:if test="e xpr -</code>	
<code>ession "> --> (After</code>	
<code>for)</code>	

Xpath	
Selecció nodes	
/	De arrel
//	Arrel (no cal direccio)
.	Actual
..	Pare del actual
@	Atribut
Funcions:	
last()	posicio Ultim node
position()	posicio node
count(node-set)	nombre de nodes

Xpath (cont)	
number sum(no-de-set)	retorna la suma
number round 8number)	
Predicats:	
/bookstore/b-ook[1]	el numero indica
/bookstore/book-[last()]	ultim
/bookstore/book-[last()-1]	penultim
/bookstore/book-[position()<3]	tots menys de 3
//title[@lang]	tots atribut lang
/bookstore/book-[price->35.00]/title	titol de llibre amb condicio

Xquery	
Variables	
<code>let \$resultat := "Hola món!"</code>	
<code>return \$resultat</code>	
DOC:	
<code>let \$d := doc('/ Use -</code>	
<code>rs/ pal amo s/G oogle</code>	
<code>Drive/M4-</code>	
<code>XML/UF 2/m ate ria l/x -</code>	
<code>que ry_ int ro/ vid -</code>	
<code>eos.xml')</code>	
<code>return \$d</code>	
FOR:	
<code>for \$a in \$doc// act -</code>	
<code>ors /actor</code>	
WHERE:	
<code>where ends-w ith(\$a,</code>	
<code>'Lisa')</code>	

