

First line

Windows Registry Editor Version 5.00

Key format

[<Hive name>\<Key name>\<Subkey name>]

@=< Value type>: <Value data>

" Value name"=< Value type>: <Value data>

Value types

@=

" Value name"="S tring value with escape charac te r s"

Deleting Keys or Values

[-<Hive name> \<Key name> \<Subkey name >] Delete Key

@- Delete
(Default)
value

" Value name"=- Delete value

The '-' character in the correct place for the Key or Value will delete it

Root Keys

HKEY_LOCAL_M- HKLM
ACHINE

HKEY_CURRENT- HKCC Win 98 & NT only
_CONFIG

HKEY_CLASSES_ROOT HKCR File associations & OLE Object
Class IDs

HKEY_CURRENT- HKCU Linked to the current User's
_USER key in HKU

(Default) HKEY_USERS HKU User profiles

value HKEY_PERFORMANC- Win NT only but invisible

String DATA

value HKEY_DYN_DATA Win 98 only

Escape characters

\ "

Precede characters with a backslash '\'

C

By **Matthew Perryman**
(PezMat)
cheatography.com/pezmat/

Not published yet.
Last updated 13th May, 2016.
Page 1 of 1.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
<http://crosswordcheats.com>