

Basic Commands

-u URL, --url=URL	Target URL (e.g. "http://www.site.com/vuln.php?id=1")
--data- =DATA	Data string to be sent through POST (e.g. "id=1")
--random-agent	Use randomly selected HTTP User-Agent header value
-p TESTPA- RAMETER	Testable parameter(s)
--level- =LEVEL	Level of tests to perform (1-5, default 1)
--risk- =RISK	Risk of tests to perform (1-3, default 1)

Enumeration Commands

-a, --all	Retrieve everything
-b, --banner	Retrieve DBMS banner
--current-user	Retrieve DBMS current user
--current-db	Retrieve DBMS current database
--passwords	Enumerate DBMS users password hashes
--dbs	Enumerate DBMS databases
--tables	Enumerate DBMS database tables
--columns	Enumerate DBMS database table columns
--schema	Enumerate DBMS schema
--dump	Dump DBMS database table entries
--dump-all	Dump all DBMS databases tables entries
--is-dba	Detect if the DBMS current user is DBA
-D <DB NAME>	DBMS database to enumerate
-T <TABLE NAME>	DBMS database table(s) to enumerate

Enumeration Commands (cont)

-C COL	DBMS database table column(s) to enumerate
-----------	--

Operating System Commands

--os-shell	Prompt for an interactive operating system shell
--os-pwn	Prompt for an OOB shell, Meterpreter or VNC
--os-cmd= OSCMD	Execute an operating system command
--priv-esc	Database process user privilege escalation
--os-smbrelay	One-click prompt for an OOB shell, Meterpreter or VNC



By QualityRubbish

cheatography.com/qualityrubbish/

Not published yet.

Last updated 28th April, 2022.

Page 1 of 1.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>