

General

```
var express = require('express');

var app = express();
```

Application

```
app.locals.title / strftime / email

app.all(path, callback)
app.use([path], callback)
app.get(path, callback)
app.post(path, callback)
app.put(path, callback)
app.delete(path, callback)
app.enable(name) : Set to True
app.disable(name) : Set to False
app.enabled(name) : True if name is True
app.disabled(name) : True if name is False
app.engine(ext, callback)
app.listen(path, callback)
app.param([name], callback)
app.render(view, [locals], callback)
app.route(path)
app.set(name, value)
app.get(name)
```

Request properties

```
req.baseUrl
req.path
req.originalUrl : req.baseUrl + req.path
req.body : Require MW body-parser & multer
req.cookies : Require MV cookie-parser
req.signedCookies : Require MV cookie-parser
req.fresh
req.stale
req.hostname
req.ip : X-Forwarded-For
req.method GET / POST / PUT / DELETE ...
req.params Properties named route parameters
req.protocol
req.query
req.route
req.secure : TLS connection
req.sockets
req.xhr : X-Requested-With
```

Request methods

Response properties

Response methods



By Maciev (shengti)
cheatography.com/shengti/

Not published yet.
Last updated 5th September, 2017.
Page 1 of 1.

Sponsored by [Readable.com](https://readable.com)
Measure your website readability!
<https://readable.com>